

SECTION II

| CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2003 | | | | | | | |
|--|--|--------------------------|-----------------------|---------------|--------------|--|---|
| (1) No. | (2) Name and Location | (3) Position | (4) Characteristic | (5) Height | (6) Range | (7) Structure | (8) Remarks |
| 16070 | Bird Island Gong Buoy 1 | 41 39 00 N 70 42 48 W | | | | Green. | Replaced by can Dec. 1 to Apr. 1. |
| | * | * | * | | * | | * 44/03 |
| 16075 | Bird Island Bell Buoy 3 | | | | | Green. | Maintained from Mar. 15 to Jan 1. |
| | * | * | * | | * | * | * 44/03 |
| 16080 | Cleveland East Ledge Light | 41 37 51 N 70 41 39 W | FI W 10s | 74 | 15 | White cylindrical tower and dwelling on red caisson. | Emergency light of reduced intensity when main light is extinguished. RACON: C (—•—•). HORN: 1 blast ev 15 (2s bl). |
| | * | * | * | * | * | * | * 44/03 |
| 16081 | Bird Island Gong Buoy 1 | | | | | | Remove from list. |
| | | | | | | | * 44/03 |
| Cleveland Ledge Channel | | | | | | | |
| 16085 | RANGE FRONT LIGHT On southern end of Abiels Ledge | 41 41 33 N 70 40 28 W | Q G | 27 | | KRW on white tower. | Visible 4° each side of rangeline. HORN: 1 blast ev 15s (2s bl). |
| | * | * | * | * | * | * | * 44/03 |
| *16090 | RANGE REAR LIGHT 3,167 yards, 015° from front light | 41 43 04 N 70 39 54 W | F G | 74 | | Visible 1.5° each side of rangeline. | KRW on white skeleton tower. |
| | | | | | | | 44/03 |
| 16095 | Lighted Bell Buoy 2 West of shoal. | 41 37 54 N 70 41 42 W | FI R 4s | | 4 | Red. | Replaced by nun when endangered by ice. |
| | * | * | * | * | * | * | * 44/03 |
| 16100 | Cleveland Ledge Channel Lighted Buoy 3 | 41 37 20 N 70 42 07 W | Q G | | | Green. | |
| | * | * | * | * | | * | * 44/03 |
| 16105 | - Lighted Buoy 4 | 41 37 18 N 70 41 57 W | Q R | | | Red. | Removed when endangered by ice. |
| | * | * | * | | * | * | * 44/03 |
| 16110 | Cleveland Ledge Oceanographic Lighted Buoy. | 41 38 36 N 70 41 00 W | FI Y 4s | | | Yellow. | Private aid. |
| | * | * | * | | * | * | * 44/03 |
| 16115 | Lighted Buoy 6 | 41 37 54 N 70 41 44 W | FI R 2.5s | | 4 | Red. | Removed when endangered by ice. |
| | * | * | * | | * | * | * 44/03 |
| 16120 | - Lighted Gong Bouy 7 Marks shoal. | 41 39 07 N 70 41 27 W | FI G 4s | | 4 | Green. | Replaced by LIB when endangered by ice. |
| | * | * | | | | | 44/03 |

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

| CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2003 | | | | | | | |
|--|----------------------------------|--------------------------|-----------------------|---------------|---------------|------------------------------------|---|
| (1) No. | (2) Name and Location | (3) Position | (4) Characteristic | (5) Height | (6) Range | (7) Structure | (8) Remarks |
| 16125 | - Lighted Buoy 8 | 41 39 06 N 70 41 17 W | FI R 4s | | 4 Red. | | Replaced by nun when endangered by ice. |
| | * | * | | | | | 44/03 |
| *22143 | Thames River Wreck Buoy WR30A | 41 27 41 N 72 04 06 W | | | Red nun. | | 44/03 |
| CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2003 | | | | | | | |
| (1) No. | (2) Name and Location | (3) Position | (4) Characteristic | (5) Height | (6) Range | (7) Structure | (8) Remarks |
| 6140 | - Warning Daybeacon | | | | | NW on pile worded DANGER SHOAL. | |
| | * | | | | | * | 44/03 |
| 31835 | - LIGHT 16 | 36 19 25 N 76 44 00 W | FI R 4s | 15 | 3 TR on pile. | | Ra ref. |
| | | * | | | | | 44/03 |
| 32115 | - LIGHT 5 | | FI G 4s | 15 | 4 SG on pile. | | |
| | | | | | * | | 44/03 |
| 32205 | - LIGHT 3 | 35 18 54 N 75 34 45 W | FI G 4s | 19 | 4 SG on pile. | | Light equipment removed when endangered by ice. |
| | | | | | * | | 44/03 |
| 32210 | - LIGHT 5 | 35 18 29 N 75 34 11 W | FI G 6s | 15 | 4 SG on pile. | | Light equipment removed when endangered by ice. |
| | | | | | * | | 44/03 |
| CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2003 | | | | | | | |
| (1) No. | (2) Name and Location | (3) Position | (4) Characteristic | (5) Height | (6) Range | (7) Structure | (8) Remarks |
| 1965 | - Channel Lighted Buoy 16 | | FI R 2.5s | | 3 Red. | | |
| | * | | * | | * | * | 44/03 |
| 2055 | - Channel Lighted Buoy 21 | | FI G 2.5s | | 3 Green. | | |
| | * | | * | | * | * | 44/03 |
| 2060 | - Channel Lighted Buoy 22 | | FI R 2.5s | | 3 Red. | | |
| | * | | * | | * | * | 44/03 |
| 2065 | - Channel Lighted Buoy 23 | | FI G 6s | | 4 Green. | | |
| | * | | * | | * | * | 44/03 |
| 2080 | - Channel Lighted Buoy 25 | | FI G 4s | | 4 Green. | | |
| | * | | * | | * | * | 44/03 |

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

| CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2003 | | | | | | | |
|--|--|--------------------------|-----------------------|---------------|--------------|------------------|-------------------|
| (1) No. | (2) Name and Location | (3) Position | (4) Characteristic | (5) Height | (6) Range | (7) Structure | (8) Remarks |
| 2085 | - Channel Lighted Buoy 26 | | FI R 6s | | 4 | Red. | |
| | * | | * | | * | * | 44/03 |
| 2105 34090 | - Channel Lighted Buoy 32 | 33 18 42 N 79 17 06 W | FI R 2.5s | 16 | 3 | TR-SY. | |
| | * | | | | | * | 44/03 |
| 34090 2105 | - Channel Lighted Buoy 32 | 33 18 42 N 79 17 06 W | FI R 2.5s | 16 | 3 | TR-SY. | |
| | * | | | | | * | 44/03 |
| *35205.2 | - Daybeacon 185 | 32 30 39 N 80 30 08 W | | | | SG-SY on pile. | |
| | | | | | | | 44/03 |
| 39545 | - LIGHT 82 | 29 42 54 N 81 14 39 W | FI R 4s | 12 | 3 | TR-TY on pile. | |
| | | * | | | | | 44/03 |
| CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2003 | | | | | | | |
| (1) No. | (2) Name and Location | (3) Position | (4) Characteristic | (5) Height | (6) Range | (7) Structure | (8) Remarks |
| 7167 | - RANGE E FRONT LIGHT | | | | | | Remove from list. |
| | | | | | | | * 44/03 |
| 7168 | - RANGE E REAR LIGHT 250 yards, 155° from front light. | | | | | | Remove from list. |
| | | | | | | | * 44/03 |
| 7170 | - LIGHT 49 | | FI G 4s | 17 | 4 | SG on pile. | Ra ref. |
| | | | * | | | | 44/03 |
| 7175 | - LIGHT 50 150 feet outside channel limit. | | FI R 4s | 17 | 4 | TR on pile. | Ra ref. |
| | | | * | | | | 44/03 |
| 7177 | - Buoy 51 | | | | | | Remove from list. |
| | | | | | | | * 44/03 |
| *7178 | - Lighted Buoy 51 | 30 20 32 N 88 34 05 W | Q G | | 3 | Green. | |
| | | | | | | | 44/03 |
| | *Delete Heading: *Pascagoula Navy Channel | | | | | | |
| 7195 | - Lighted Buoy 1 | | | | | | Remove from list. |
| | | | | | | | * 44/03 |

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

| CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2003 | | | | | | | |
|---|---|--------------------------|-----------------------|---------------|--------------|-------------------------------|-------------------|
| (1) No. | (2) Name and Location | (3) Position | (4) Characteristic | (5) Height | (6) Range | (7) Structure | (8) Remarks |
| *7196 | - Buoy 1 | 30 20 32 N 88 34 26 W | | | | Green can. | |
| | | | | | | | 44/03 |
| 7200 | - Buoy 1A | | | | | | Remove from list. |
| | | | | | | | * |
| | | | | | | | 44/03 |
| 7202 | - SINGING ISLAND LIGHT A | | | | | | Remove from list. |
| | | | | | | | * |
| | | | | | | | 44/03 |
| | *Delete Heading: *Pascagoula Channel | | | | | | |
| 7205 | - LIGHT | 30 20 18 N 88 34 30 W | FI W 4s | 22 | 5 | NG on tower. | Ra ref. |
| | | | | | | | 44/03 |
| 38580 | - Buoy 143 | 27 25 56 N 97 20 46 W | | | | Green can with yellow square. | |
| | | * | | | | | 44/03 |

| CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2003 | | | | | | | |
|---|----------------------------------|---------------------------|-----------------------|---------------|--------------|-----------------------|--|
| (1) No. | (2) Name and Location | (3) Position | (4) Characteristic | (5) Height | (6) Range | (7) Structure | (8) Remarks |
| 4180 | - Lighted Bell Buoy 5 | 37 46 38 N 122 36 22 W | FI G 6s | | 5 | Green. | |
| | | * | | | | | 44/03 |
| 8625 | - ENTRANCE LIGHT 5 | 42 02 36 N 124 16 21 W | FI G 4s | 23 | 3 | Green pile structure. | Due to weather conditions the dayboards have been removed from this aid. |
| | | | | | * | | 44/03 |
| 16770 | SHILSHOLE BAY BOAT BASIN LIGHT 2 | 47 41 16 N 122 24 18 W | FI R 2.5s | 28 | 5 | TR on jetty. | |
| | | | * | * | | | 44/03 |
| 16790 18140 | SHILSHOLE BAY BREAKWATER LIGHT 3 | 47 40 38 N 122 24 43 W | FI G 2.5s | 29 | 5 | SG on white house. | |
| | | | | * | | | 44/03 |
| 18140 16790 | - BREAKWATER LIGHT 3 | 47 40 38 N 122 24 43 W | FI G 2.5s | 29 | 5 | SG on white house. | |
| | | | | * | | | 44/03 |
| 19920 | - LIGHT 4 | 48 59 32 N 122 47 02 W | FI R 6s | 15 | 4 | TR on pile structure. | |
| | | * | | | * | | * |
| | | | | | | | 44/03 |

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

| CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2003 | | | | | | | | |
|--|--|--------------------------|--|---------------|--------------|---|--|-------|
| (1) No. | (2) Name and Location | (3) Position | (4) Characteristic | (5) Height | (6) Range | (7) Structure | (8) Remarks | |
| 2080 | - West Pierhead Light | 43 28 24 N 76 31 00 W | Al WR 10s 0.1s W. fl 4.9s ec. 0.1s W. fl 4.9s ec. | 57 17 | 12 | White square tower on corner of square building. | Standby light Oc R 4s of reduced intensity. HORN: 1 blast ev 30s (3s bl). Operates from Apr. 1 to Oct 15. | |
| | | | | | | | * | 44/03 |
| 2680 | - Light | | Al WG 10s | 71 22 | W 22 G 18 | White tower. | HORN: 2 blasts ev 30s (2s bl-2s si-2s bl-24s si). Operates from Apr. 1 to Oct 15. | |
| | | | | | | | * | 44/03 |
| 3870 | - West Breakwater Light | | Iso W 6s | 56 17 | 10 | Tower. | HORN: 2 blasts ev 30s (2s bl-2s si-2s bl-24s si). Operates from Apr. 1 to Oct 15. | |
| | | | * | | | | * | 44/03 |
| 4725 | - RANGE FRONT LIGHT | 41 28 36 N 82 41 48 W | Q G | 33 10 | 9 | KRW on skeleton tower. | Visible on range line only. Higher intensity on rangeline only. | |
| | | | * | | | | | 44/03 |
| *Delete Note: | | | | | | | | |
| Selfridge Launch Facility | | | | | | | | |
| <i>*Aids maintained from Apr. 15 to Nov. 1.</i> | | | | | | | | |
| 9162 | SELFRIDGE MARINA ENTRANCE LIGHT 1 | 42 36 58 N 82 49 06 W | FI R 4s | 20 6 | 4 | SG on pile. | | |
| | | * | * | * | | | | 44/03 |
| 9163 | SELFRIDGE MARINA ENTRANCE LIGHT 2 | 42 36 59 N 82 49 06 W | FI R 4s | 20 6 | 4 | TR on pile. | | |
| | | * | * | * | | | | 44/03 |
| 19051 | <i>Lighted Buoy 15A</i> | 43 04 19 N 86 12 33 W | FI G 6s | | 4 | Green. | Maintained from April 1 to Nov. 1. | |
| | * | | | | | | | 44/03 |
| 19800 | - Harbor Breakwater South End Light | 41 43 34 N 87 29 36 W | Al WR 10s 0.2s W fl 4.8s ec. 0.2s R fl 4.8s ec. | 50 15 | W 17 R 14 | White square skeleton tower with red band. Lower half open. | HORN: 1 blast ev 15s (2s bl). Operates continuously from Apr. to Dec. | |
| | | | | | * | | | 44/03 |
| 19827 | - HARBOR BREAKWATER OBSTRUCTION LIGHT | 41 44 29 N 87 30 52 W | FI Y 2.5s | 28 9 | 8 | White cylindrical tower with yellow band. | | |
| | | | * | | | | | 44/03 |
| *Change Heading to Read: | | | | | | | | |
| *Green Bay Harbor | | | | | | | | |
| 22272 | - ENTRANCE LIGHT 1 | 44 32 21 N 88 00 12 W | F G | 11 3 | | SG on pile. | Private aid. | |
| | | | * | | | | | 44/03 |

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2003

| (1) No. | (2) Name and Location | (3) Position | (4) Characteristic | (5) Height | (6) Range | (7) Structure | (8) Remarks |
|------------|--------------------------|--------------------------|-----------------------|----------------|--------------|------------------|----------------|
| 22273 | - ENTRANCE LIGHT 2 | 44 32 20 N 88 00 12 W | F R | 11 3 | TR on pile. | | Private aid. |

*

44/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.